This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

1. (Currently Amended) A method for a computer system for providing communication between a first system and a second system, wherein the first system uses <u>IPv4 (Internet Protocol version 4)</u> a first-version of a protocol and the second system uses <u>IPv6 (Internet Protocol version 6)</u> a second version of the protocol, the method comprising:

providing a first application on the first system;

inserting an <u>Application Programming Interface (API)</u> <del>API</del> level translator layer, wherein the API level translator layer does not require a stack for <u>IPv6</u> the second version of the protocol;

making a function call to a socket Application Programming Interface (API) for IPv4 the first version:

intercepting the function call by the API level translator layer, wherein interception of the function call is not required to occur after a packet is passed to an IPv4 stack;

translating the function call to a translated function call wherein the translated function call uses raw sockets;

making a function call to the socket API for the translated function call that uses raw sockets: and

setting the socket option on the raw socket to supply new IP headers;

passing a packet to a stack for <u>IPv4</u> the first version of the protocol;

providing an alternate implementation for a sending-related IPv4 socket function, wherein the alternate implementation comprises:

intercepting an IPv4 socket API call to send a packet; translating the IPv4 socket API call to use a raw socket; Appl. No. 10/637,408 Amdt. dated October 16, 2007 Reply to Office Action of July 17, 2007

providing transport and IPv6 headers ahead of user supplied payload data; fragmenting the packet as required; calling a corresponding IPv4 socket API function for the raw socket; and

providing an alternate implementation for a reception-related IPv4 socket function, wherein the alternate implementation comprises:

receiving an incoming packet on a raw socket;

passing the packet to the stack; and

checking a source host to determine the proper destination for the incoming packet as required;

checking a port number for the incoming packet; stripping transport and IP headers from the incoming packet; and passing a payload to a destination application.

- 2. (Canceled)
- 3. (Canceled)
- 4. (Currently Amended) The method of claim  $\underline{1}$  2, further comprising supplying IP headers only once.
- 5. (Currently Amended) The method of claim  $\underline{1}$  2, wherein the method is implemented by inserting an API level translator layer between a socket API layer and a TCP/IPv4 layer.
- 6. (Currently Amended) The method of claim  $\underline{1}$  2, wherein the method is implemented without using an IPv6 stack.

Appl. No. 10/637,408 Amdt. dated October 16, 2007

Reply to Office Action of July 17, 2007

7. (Original) The method of claim 4, further comprising passing the packet to a network

card driver.

8. (Canceled)

9. (Currently Amended) The method of claim 12, further comprising performing tunneling

of IPv6 packets over IPv4 routing infrastructure.

10. (Currently Amended) The method of claim 12, further comprising using a Name

Resolver service to perform name to address resolution related functions.

11. (Original) The method of claim 10, wherein the Name Resolver service is configured to

run on a separate host that includes an IPv4 stack and an IPv6 stack.

12. (Original) The method of claim 11, wherein name to address resolution functions of the

Name Resolver service use the IPv6 stack.

13. (Original) The method of claim 12, wherein the Name Resolver service is further

configured to receive a query from the first system, use the address resolution functions to obtain

a record and send the record to the first system.

14. (Canceled)

15. (Canceled)

16. (Currently Amended) The method of claim 1 14, further comprising fragmenting the

packet.

Page 4 of 15

- 17. (Currently Amended) The method of claim  $\underline{1}$  14, further comprising passing the packet to a network card driver.
- 18. (Currently Amended) A set of executable instructions on a computer readable medium for providing communication between an IPv4 (Internet Protocol version 4) system and an IPv6 (Internet Protocol version 6) system, the instructions being configured to:

provide an IPv4 application on the IPv4 system;

insert an <u>Application Programming Interface (API)</u> API level translator layer, wherein the API level translator layer does not require a stack for <u>IPv6</u> the second version of the protocol;

make a function call to an IPv4 socket Application Programming Interface (API);

translate the function call to a translated function call wherein the translated function call uses raw sockets;

make another function call to the IPv4 socket API for the translated function call that uses raw sockets: and

set the socket option on the raw socket to supply new IP headers;

pass a packet to an IPv4 stack;

provide an alternate implementation for a sending-related IPv4 socket function, wherein the alternate implementation comprises:

intercepting an IPv4 socket API call to send a packet;

translating the IPv4 socket API call to use a raw socket;

providing transport and IPv6 headers ahead of user supplied payload data;

fragmenting the packet as required;

calling a corresponding IPv4 socket API function for the raw socket; and passing the packet to the stack; and

provide an alternate implementation for a reception-related IPv4 socket function, wherein the alternate implementation comprises:

receiving an incoming packet on a raw socket;

checking a source host to determine the proper destination for the incoming packet as required;

checking a port number for the incoming packet; stripping transport and IP headers from the incoming packet; and passing a payload to the IPv4 application.

- 19. (Original) The set of executable instructions of claim 18, wherein the method further comprises supplying IP headers only once.
- 20. (Original) The set of executable instructions of claim 18, wherein the method is implemented by inserting an API level translator layer between a socket API layer and a TCP/IPv4 layer.
- 21. (Original) The set of executable instructions of claim 18, wherein the method is implemented without using an IPv6 stack.
- 22. (Canceled)
- 23. (Canceled)
- 24. (Canceled)
- 25. (Currently Amended) The set of executable instructions of claim <u>18</u> 24, wherein the method further comprises performing tunneling of IPv6 packets over IPv4 routing infrastructure.

- 26. (Currently Amended) The set of executable instructions of claim <u>18</u> 24, wherein the method further comprises fragmenting the packet.
- 27. (Currently Amended) The set of executable instructions of claim <u>18</u> 24, wherein the method further comprises passing the packet to a network card driver.
- 28. (Currently Amended) A system for enabling an IPv4 (Internet Protocol version 4) application to communicate across a computer network using an IPv6 (Internet Protocol version 6) system, the system comprising:

a computing device;

executable instructions executable on the computing device, wherein the executable instructions are configured to implement a method comprising:

insert inserting an Application Programming Interface (API) API level translator layer, wherein the API level translator layer does not require a stack for IPv6 the second version of the protocol;

make making a function call to an IPv4 socket Application Programming Interface (API);

<u>translate</u> translating the function call to a translated function call wherein the translated function call uses raw sockets;

make making another function call to the IPv4 socket API for the translated function call that uses raw sockets; and

set the socket option on the raw socket to supply new IP headers;

pass passing a packet to an IPv4 stack;

provide an alternate implementation for a sending-related IPv4 socket function,
wherein the alternate implementation comprises:
intercepting an IPv4 socket API call to send a packet;

Appl. No. 10/637,408 Amdt. dated October 16, 2007 Reply to Office Action of July 17, 2007

translating the IPv4 socket API call to use a raw socket;
providing transport and IPv6 headers ahead of user supplied payload data;
fragmenting the packet as required;
calling a corresponding IPv4 socket API function for the raw socket; and
passing the packet to the stack; and

provide an alternate implementation for a reception-related IPv4 socket function, wherein the alternate implementation comprises:

receiving an incoming packet on a raw socket;

checking a source host to determine the proper destination for the incoming packet as required;

checking a port number for the incoming packet; stripping transport and IP headers from the incoming packet; and passing a payload to the IPv4 application.

- 29. (Original) The system of claim 28, further comprising an API level translator layer between a socket API layer and a TCP/IPv4 layer.
- 30. (Canceled)
- 31. (Canceled)
- 32. (Original) The system of claim 28, wherein the method further comprises performing tunneling of IPv6 packets over IPv4 routing infrastructure.
- 33. (Original) The system of claim 28, wherein the method further comprises fragmenting the packet.